

"VILLAGE GREEN"

40B COMPREHENSIVE PERMIT AMENDED APPLICATION

at 15 Great Road

Littleton, Massachusetts

RECEIVED
2-12-14

NOTE:

ALL SUPPLEMENTAL DATA SUBMITTED IN CONJUNCTION WITH THIS 40B COMPREHENSIVE PERMIT APPLICATION AS REQUIRED BY THE LITTLETON ZONING BOARD OF APPEALS IS HEREBY INCORPORATED AS PART OF THE PLAN SET. THIS PLAN, ITS SUPPORTING DOCUMENTATION AND FORM WORK ARE SUBMITTED PURSUANT TO THE PROVISIONS OF THE TOWN OF LITTLETON'S ZONING BOARD OF APPEALS MODEL RULES FOR THE ISSUANCE OF A COMPREHENSIVE PERMIT AND MASSACHUSETTS GENERAL LAW, CHAPTER 40B.



LITTLETON ASSESSOR DATA:
MAP & PARCEL: MAP U1 PARCELS
2-0, 6-0 AND 32-20.

REFERENCES:
MIDDLESEX SOUTH REGISTRY OF DEEDS
BK 62302 PG 405
BK 62302 PG 407
BK 62302 PG 409

ZONING
R-RESIDENTIAL

SITE DOES NOT CONTAIN ANY FLOOD HAZARD ZONE PER FLOOD INSURANCE RATE MAP 25017C243E PANEL 243 OF 656 EFFECTIVE JUNE 4, 2010.

SITE IS NOT WITHIN A LITTLETON AQUIFER OR WATERSHED PROTECTION OVERLAY DISTRICT.




APPLICANT:
Fifteen Great Road II LLC
200 Baker Avenue—Suite 303
Concord, MA 01742

OWNER:
Fifteen Great Road II LLC
C/O Omni properties, LLC
200 Baker Ave, Suite 303
Concord, MA 01742

PLANNER, LANDSCAPE ARCHITECT, CIVIL ENGINEER & SURVEYOR:
Places Associates, Inc.
256 Great Road, Suite 4
Littleton, MA 01460

ARCHITECTS:
David M. White, Architect
54 Todd Farm Lane
P.O.Box 817
New London, NH 03257

Artform Architecture, Inc.
580 Greenland Road
Portsmouth, NH 03801



SHEET INDEX


CP-1	COVER SHEET
ANR	SURVEY PLAN
CP-2	NOTES AND LEGEND
CP-3	INDEX PLAN
CP-4,5	LAYOUT AND UTILITIES PLANS
CP-6,7	GRADING AND DRAINAGE PLANS
CP-8	WAIVER PLAN
CP-9-14	CONSTRUCTION DETAILS
CP-15	E&S PLAN
CP-16	SIGNAGE PLAN
CP-17	COMMON INFRASTRUCTURE PLAN
L-1,2	LANDSCAPE PLANS
BE-1&2	BUILDING ENVELOPE DETAILS

GENERAL REVISION NOTE:
PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERSEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION.

COVER SHEET
LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:
FIFTEEN GREAT ROAD II LLC
SCALE: AS SHOWN DATE: FEB 4, 2014
Places Associates, Inc.
Planning, Landscape Architecture, Civil Engineering, Surveying
256 GREAT ROAD, SUITE 4 LITTLETON, MA 01460 978.486.0334 Ph. 978.486.0447 Fax places@cesassociates.com
PROJECT No. 11-6303A PLAN No. 6303A CP-1

PERMIT SET
NOT FOR CONSTRUCTION



GENERAL NOTES:

- PRIOR TO THE PREPARATION OF BIDS AND/OR THE INITIATION OF CONSTRUCTION, THE CONTRACTOR SHALL OBTAIN AND CAREFULLY EXAMINE THIS PLAN SET, RELATED CONSTRUCTION PLAN SETS FROM OTHER PROFESSIONAL DISCIPLINES, CONSTRUCTION SPECIFICATIONS, MANUFACTURERS INFORMATION AND ANY APPLICABLE PERMIT REQUIREMENTS/CONDITIONS OF APPROVAL FOR THE PROJECT. SEE NOTE #4 BELOW, AS IT RELATES TO THIS REQUIREMENT.
- THE EXISTING UTILITIES SHOWN ON THESE PLANS ARE APPROXIMATE ONLY. DIG SAFE AND THE APPROPRIATE UTILITY COMPANIES SHALL BE CONTACTED BY THE CONTRACTOR PRIOR TO THE INITIATION OF CONSTRUCTION OR ANY EXCAVATION.
- NOT ALL UTILITIES WERE ABLE TO BE LOCATED BY RECORD INFORMATION, SITE SURVEYS OR UTILITY LOCATOR SERVICES. THE DESIGN ENGINEER AND BASE PLAN SURVEYOR DO NOT ACCEPT ANY RESPONSIBILITY FOR DAMAGES INCURRED AS A RESULT OF UTILITIES OR SUBSURFACE STRUCTURES WHICH ARE OMITTED OR INACCURATELY SHOWN. PRIOR TO THE INITIATION OF WORK, THE CONTRACTOR SHALL VERIFY THE LOCATION/ELEVATION OF EXISTING UTILITIES SHOWN ON THE PLAN.
- THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY UPON THE DISCOVERY OF ANY DISCREPANCY BETWEEN THE LOCATION/ELEVATION OF ANY EXISTING UTILITIES SHOWN ON THE PLANS AND THAT WHICH IS FOUND IN THE FIELD.
- THE CONTRACTOR SHALL RETAIN THE SERVICES OF A REGISTERED PROFESSIONAL LAND SURVEYOR TO PROVIDE LAYOUT & CONTROL FOR THE DEVELOPMENT OF THE SITE.
- THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY UPON THE DISCOVERY OF ANY CONTRADICTORY, INCOMPLETE OR MISLABELED INFORMATION SHOWN ON THE PLANS OR PLANS PREPARED BY OTHERS. THE CONTRACTOR SHALL ALLOW FOR ADEQUATE TIME FOR THE ENGINEER TO RESPOND/PROVIDE DIRECTION FOR THE PLAN DISCREPANCY.
- ALL CONSTRUCTION UNDER AREAS SUBJECT TO VEHICULAR TRAFFIC SHALL BE CONSTRUCTED TO WITHSTAND A DIRECT AASHTO H20 DESIGN LOAD. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROTECT ALL UTILITY/SITE IMPROVEMENT AREAS UNDER LANDSCAPED/NON-TRAFFIC BEARING AREAS FROM TEMPORARY CONSTRUCTION LOADS DURING CONSTRUCTION.
- THE CONSTRUCTION SHOWN ON THESE PLANS REQUIRES AN ORDER OF CONDITIONS BE ISSUED BY THE LITTLETON CONSERVATION COMMISSION. THE CONTRACTOR SHALL OBTAIN A COPY OF SUCH ORDERS OF CONDITIONS PRIOR TO ANY SITE-RELATED DISTURBANCES AND SHALL COMPLY WITH APPROPRIATE CONDITIONS FOR CONSTRUCTION.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL ADJACENT PROPERTY FROM DAMAGE. ALL DAMAGES BY THE CONTRACTOR OR SUBCONTRACTORS SHALL BE REPAID AT NO COST TO THE OWNER. PRE-CONSTRUCTION PHOTOS SHALL BE TAKEN AND COPIES SUPPLIED TO THE ENGINEER, PRIOR TO ANY SITE CONSTRUCTION AND OR DISTURBANCE.
- THE CONTRACTOR SHALL MAINTAIN AND PROTECT ALL EXISTING SURVEY MONUMENTS (BOUNDS, PINS, PIPES, DRILL HOLES, ETC.) THROUGHOUT ALL PHASES OF CONSTRUCTION. ANY DISTURBED MONUMENTS SHALL BE REPLACED BY A REGISTERED PROFESSIONAL LAND SURVEYOR AT THE EXPENSE OF THE CONTRACTOR.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING SHOP DRAWINGS OF PRODUCTS/MATERIALS TO THE ENGINEER AND/OR THE LOCAL APPROVING AUTHORITY AS REQUIRED IN THE CONSTRUCTION DOCUMENTS OR IF REQUIRED BY THE LOCAL AUTHORITY HAVING JURISDICTION OVER THE PRODUCT. ADEQUATE TIME SHALL BE ALLOWED FOR THE SHOP DRAWINGS TO BE REVIEWED AND RETURNED TO THE CONTRACTOR PRIOR TO ORDERING THE SPECIFIED PRODUCTS/MATERIALS.
- ALL SUPPLEMENTAL DATA SUBMITTED IN CONJUNCTION WITH THIS PLAN SET AS REQUIRED BY THE APPROPRIATE REGULATIONS IS HEREBY INCORPORATED AS PART OF THE PLAN SET.
- ALL PERMANENT BOUNDARY AND SURVEY MONUMENTS SHALL BE INSTALLED AFTER THE COMPLETION OF ALL HEAVY SITE WORK.
- NO DEBRIS, JUNK, RUBBISH OR OTHER WASTE MATERIALS SHALL BE BURIED, BURNED OR OTHERWISE DISPOSED OF WITHIN THE LIMITS OF THE PROJECT. ALL WASTE, TRASH AND DEBRIS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF IN ACCORDANCE WITH APPLICABLE LAWS.
- UNLESS OTHERWISE SPECIFIED OR SHOWN, ALL CONSTRUCTION METHODS AND MATERIALS SHALL CONFORM TO THE STANDARDS DESCRIBED IN THE TOWN OF LITTLETON'S SUBDIVISION CONTROL REGULATIONS. IF NOT SPECIFIED THEREIN, SUCH CONSTRUCTION SHALL THEN CONFORM TO THE REQUIREMENTS OF THE MASSACHUSETTS DEPARTMENT OF TRANSPORTATION (MDOT, FORMERLY MASSHIGHWAY) STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES, LATEST VERSION.
- THE CONTRACTOR SHALL APPLY FOR AND OBTAIN A PERMIT FROM MASS HIGHWAY TO CONSTRUCT WITHIN A PUBLIC WAY FOR WORK WITHIN GREAT ROAD, STATE ROUTE 2A. CONTROLLED DENSITY FILL SHALL BE USED AS PAVEMENT BASE COURSE WITHIN THE STATE HIGHWAY LAYOUT.
- WETLANDS DELINEATION PERFORMED BY OXBOW ASSOCIATES, INC OF ACTON, MA IN APRIL 2011. LOCATIONS OF FLAGS WERE FIELD-SURVEY LOCATED BY PLACES ASSOCIATES, INC. THE FINAL WETLANDS LIMITS ARE SUBJECT TO REVIEW AND APPROVAL BY THE LITTLETON CONSERVATION COMMISSION, SEE NOTE #8 ABOVE.

SITE WORK NOTES:

- THE LIMITS OF WORK SHALL BE FIELD ESTABLISHED PRIOR TO INITIATION OF ANY CONSTRUCTION, SITE EXPLORATIONS OR EARTHEN DISTURBANCE.
- EROSION CONTROLS SHALL BE IMPLEMENTED PRIOR TO SITE CLEARING OR DISTURBANCE. SEE EROSION AND SEDIMENTATION CONTROL PLAN.
- EXCEPT FOR THE SETUP FOR ENTRY TO THE SITE, NO CONSTRUCTION OR CONTRACTOR'S VEHICLES SHALL BE PARKED ON GRIST MILL ROAD OR GREAT ROAD, UNLESS COORDINATED WITH ADJACENT PROPERTY OWNERS. ALL CONSTRUCTION STAGING, STOCKPILE AND PARKING AREAS SHALL BE ON SITE.
- LOAM SHALL BE STOCKPILED FOR RE-USE ON THE SITE TO THE EXTENT PRACTICAL, SEE EROSION AND SEDIMENTATION CONTROL PLAN.
- NO DEBRIS, JUNK, RUBBISH OR OTHER WASTE MATERIALS SHALL BE BURIED, BURNED OR OTHERWISE DISPOSED OF WITHIN THE LIMITS OF THE PROJECT. ALL WASTE, TRASH AND DEBRIS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF IN ACCORDANCE WITH APPLICABLE LAWS. THE SITE SHALL BE KEPT IN A NEAT AND ORDERLY FASHION.
- THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TRENCH OPERATIONS PERMIT PURSUANT TO THE REQUIREMENTS OF THE TOWN OF LITTLETON AND 520 CMR 14.00 TRENCH SAFETY REGULATIONS.

MATERIAL DEFINITIONS:

BITUMINOUS CONCRETE PAVEMENT ALL SITE PAVING SHALL BE CLASS 1 BITUMINOUS CONCRETE. MIXTURES SHALL BE COMPOSED OF NATURAL AGGREGATE, FINE FILLER (IF REQUIRED) AND BITUMINOUS MATERIAL. SITE MIXTURE MAY BE USED AS RECLAMED PAVEMENT AT THE OPTION OF THE CONTRACTOR AND AS PRE-APPROVED BY LITTLETON HIGHWAY DEPARTMENT.

THE MIXTURE COMPOSITION AND TOLERANCES SHALL MEET THE SPECIFICATIONS FOR BINDER COURSE AND TOP COURSE MIXTURES AS SPECIFIED IN TABLE A OF SSIB M2.11.03. IF RECLAMED ASPHALT PAVEMENT (RAP) IS USED IN THE MIXTURE, THE PROPORTION OF RAP TO VIRGIN AGGREGATE SHALL BE LIMITED TO A MAXIMUM OF 40% FOR DRUM MIX PLANTS AND 20% FOR MOORED BATCH PLANTS.

CAST IN PLACE CONCRETE

ALL SITE CAST IN PLACE CONCRETE AND RELATED REINFORCING SHALL MEET THE REQUIREMENTS OF THE MASSACHUSETTS STATE BUILDING CODE, THE AMERICAN CONCRETE INSTITUTE (ACI) AND THE AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) FOR PRODUCT MATERIALS, FORM WORK, PLACEMENT AND CURING. ALL SITE CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4,000 PSI UNLESS OTHERWISE REQUIRED IN THE CONSTRUCTION DOCUMENTS.

CONTROLLED DENSITY FILL (CDF)

CONTROL DENSITY FILL SHALL BE A FLOWABLE, SELF-COMPACTING, RIGID SETTING, LOW DENSITY MATERIAL THAT CAN SUBSTITUTE FOR COMPACTED GRAVELS FOR BACKFILLS, FILLS AND STRUCTURAL FILLS. CDF SHALL BE EXCAVATED BY HAND TOOLS AND/OR SMALL EQUIPMENT WHEN PLACED AND CURED. CDF SHALL MEET THE REQUIREMENTS OF SSIB M4.2.08, TYPE 2E, AND SHALL MEET THE FOLLOWING REQUIREMENTS:

A. CDF IS TO BE BATCHED AT A READY MIX PLANT AND IS TO BE USED AT A HIGH OF "VERY HIGH SLUMP" FROM 10' TO 12'. IT SHALL BE FLOWABLE AND REQUIRE NO VIBRATION AFTER IT HAS BEEN PLACED.

B. CDF SHALL BE A MIXTURE OF PORTLAND CEMENT, FLYASH, SAND AND WATER DESIGNED TO MEET THE CDF REQUIREMENTS. HIGH AIR ENTRAINMENT MAY BE SUBSTITUTED FOR FLYASH WITH AN ADJUSTMENTS (25%) ADJUSTMENT IN SAND CONTENT.

C. CDF MUST MEET THE FOLLOWING STRENGTH REQUIREMENTS:
-28 DAY COMPRESSIVE STRENGTH: 30-60 PSI
-90 DAY COMPRESSIVE STRENGTH: 100 PSI MAX

CRUSHED STONE

CRUSHED STONE SHALL BE THE SIZE AS INDICATED ON THE PLANS. THE STONE SHALL BE FROM STONE QUARRIES THAT PRODUCE HARD, ANGULAR, DURABLE, WASHED STONE FREE FROM DEBRIS AND ORGANIC MATERIALS. THE STONE SHALL MEET THE REQUIREMENTS OF SSIB M2.0.01.0

DENSE GRADED CRUSHED STONE

DENSE GRADED CRUSHED STONE SHALL CONSIST OF THE COMBINATION OF CRUSHER-RUN COARSE AGGREGATES (MEETING SSIB M2.0.01.0) AND FINE AGGREGATES OF NATURAL SAND OR STONE SCREENING UNPREDICED IN SIZE. THE DENSE GRADED CRUSHED STONE SHALL CONSIST OF HARD, DURABLE PARCELS OF FRAGMENTS OF STONE MATERIALS THAT BREAK UP WHEN ALTERNATELY FROZEN AND THAWED OR WETTED AND DRIED. SHALE SHALL NOT BE USED. FINE AGGREGATE SHALL CONSIST OF NATURAL OR CRUSHED SAND. THE GRADATION/MATERIAL SHALL COMPLY WITH THE SPECIFICATIONS OF SSIB M2.0.1.7

GLACIAL TILL

A. GLACIAL TILL: NATURAL INORGANIC SOIL APPROVED BY THE ENGINEER AND MEETING THE FOLLOWING REQUIREMENTS:

A. IT SHALL BE FREE OF ORGANIC OR OTHER HEAVY OR COMPRESSIBLE MATERIALS, DEBRIS AND STONES GREATER THAN TWO INCHES IN MAXIMUM DIMENSION.

B. IT SHALL BE A SILT LOAM AS DEFINED BY THE U.S. DEPARTMENT OF AGRICULTURE SOIL TEXTURAL CLASSIFICATION.

C. THE SOIL SHALL CONSIST OF GREATER THAN 50% SILT, 12% TO 27% CLAY, OR 50% TO 80% SILT AND LESS THAN 12% CLAY.

GRAVEL BORROW

GRAVEL BORROW SHALL CONSIST OF INERT MATERIAL THAT IS HARD, DURABLE AND DELETERIOUS MATERIAL, FREE FROM CLAY, SURFACE COATINGS, ORGANIC AND DELETERIOUS MATERIAL. ALL GRAVEL BORROW SHALL MEET THE REQUIREMENTS OF SSIB M2.0.01.0. MAXIMUM STONE SIZE SHALL BE AS FOLLOWS:

TYPE A: 6" LARGEST DIMENSION
TYPE B: 3" LARGEST DIMENSION
TYPE C: 2" LARGEST DIMENSION

LOAM (BORROW)

LOAM SHALL CONSIST OF NATURAL TOPSOIL, FREE FROM SUB-SOIL, OBTAINED FROM AN AREA WHICH HAS NEVER BEEN STRIPPED. LOAM SHALL BE OF UNIFORM QUALITY, FREE FROM HARD CLODS, STIFF CLAY, HARDPAN, SOIL, IRREGULAR DISINTINUED STONES, LIME, CEMENT, ASHES, SLAG, CONCRETE, TAR RESIN, TARNED PAPER, BOARDS, CHIPS OR ANY OTHER UNDESIRABLE MATERIAL.

LOAM SHALL CONTAIN BETWEEN 5.0 AND 7.5 PERCENT ORGANIC MATTER AS DETERMINED BY THE CURRENT METHOD OF THE ASSOCIATION OF OFFICIAL AGRICULTURAL CHEMISTS.

THE ACIDITY RANGE OF THE LOAM SHALL BE PH 6.5 TO PH 7.5 INCLUSIVE.

THE MECHANICAL ANALYSIS OF THE SOIL SHALL BE AS FOLLOWS:

U.S. SIEVE SIZE & NUMBER	PERCENT PASSING	MAXIMUM
1 INCH	100%	100%
1/2 INCH	97%	100%
NO. 100 (SAND)	45%	60%
NO. 100 (SILT & CLAY)	40%	60%

ORDINARY BORROW

ORDINARY BORROW SHALL CONSIST OF MATERIAL NOT SPECIFIED AS ANY OTHER EARTHEN MATERIAL. ORDINARY BORROW SHALL BE WELL GRADED, NATURAL, INORGANIC MATERIAL ACCEPTABLE TO THE ENGINEER FOR THE GENERAL FILLING TO THE SPECIFIED SUB-GRADE. THE MATERIAL SHALL MEET THE FOLLOWING REQUIREMENTS:

A. IT SHALL BE FREE OF ORGANIC OR OTHER HEAVY OR COMPRESSIBLE MATERIALS AND OF FROZEN MATERIALS AND OF STONES LARGER THAN 8 INCHES IN MAXIMUM DIMENSION.

B. IT SHALL BE OF SUCH NATURE & CHARACTER THAT IT CAN BE COMPACTED TO THE SPECIFIED DENSITIES IN A REASONABLE AMOUNT OF TIME.

C. IT SHALL BE FREE OF HIGH PLASTIC CLAY, OF ALL MATERIALS SUBJECT TO DESTRUCTIVE DEGRADATION AND OF OTHERS MATERIALS WHICH WILL CORRODE PIPING OR OTHER BURIED MATERIALS.

D. IT SHALL HAVE A MAXIMUM DRY DENSITY OF NOT LESS THAN 100 POUNDS PER CUBIC YARD AND LESS THAN 40 % OF THE MATERIAL SHALL PASS THE NUMBER 200 SIEVE.

E. EXCAVATED ROCK & BOULDERS SMALLER THAN ONE CUBIC YARD IN SIZE MAY BE USED IN FILL AREAS UNLESS LAYED ONLY PROVIDED THEY ARE COVERED WITH A MINIMUM OF 12" OF SOIL, DRAINED, PLACED AND COMPACTED IN LAYERS WITH NO Voids AND ALL INTERSTICES FILLED.

RIP RAP

RIP RAP STONE SHALL BE SOUND, DURABLE ROCK, ANGULAR IN SHAPE, RIP RAPED STONES, BOULDERS, POSITIONED ON SOLID SOIL STONE OR ROCK. THE STONES MAY NOT BE PLACED IN A MANNER UNUSUALLY PERMITTED BY THE DESIGN ENGINEER. ALL RIP RAP MATERIALS SHALL MEET THE REQUIREMENTS OF SSIB M2.0.02.0.

SAND BORROW

SAND BORROW SHALL CONSIST OF CLEAN INERT, HARD, DURABLE GRAINS OF QUARTZ OR OTHER HARD DURABLE ROCK, FREE FROM LOAM OR CLAY, SILICATE COATINGS AND DELETERIOUS MATERIALS. THE ALLOWED DRY DENSITY OF MATERIAL PASSING THE 7.5" SIEVE AS DETERMINED BY ASTM D1885, METHOD C, SHALL NOT EXCEED 100 MASS. ALL SAND BORROW SHALL MEET THE REQUIREMENTS OF SSIB M1.04.0.

COMPACTION TESTING

ALL EARTHEN MATERIALS SHALL BE COMPACTED TO THE DRY DENSITY INDICATED IN THE CONSTRUCTION DOCUMENTS AND AS IS DETERMINED BY CODE OR REGULATION. MAXIMUM DRY DENSITY SHALL BE DETERMINED FROM A SAMPLE OF THE MATERIAL TO BE USED AND TESTED IN ACCORDANCE WITH THE MODIFIED PROCTOR DRY DENSITY TEST AS DEFINED IN ASTM D1885, METHOD C.

AREAS THAT WERE TESTED AND FOUND TO BE INSUFFICIENTLY COMPACTED SHALL BE RE-TESTED AFTER THE ADDITIONAL COMPACTION HAS BEEN COMPLETED.

ABBREVIATIONS:

AASHTO AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS
ABR ACCESSIBLE RAMP - TYPE 1
AR-1 ACCESSIBLE RAMP - TYPE 2
AR-2 ACCESSIBLE RAMP - TYPE 3
ASTM AMERICAN SOCIETY FOR TESTING AND MATERIALS

BAB BAG & BURLAP
BC BITUMINOUS CONCRETE
BIG BENCHMARK
BR BOTTOM RAMP ELEVATION
CAL CALIPER
CB CONCRETE BOUND
CF CUBIC FOOT
CI CAST IRON PIPE
CMP CORRUGATED METAL PIPE
CONC CONCRETE
CTB CUBIC YARD
DR DRILL HOLE
DI DUCTILE IRON PIPE
DM DRAIN
DMM DRAIN MANHOLE
ELEV ELEVATION
EMH ELECTRIC MANHOLE
EX EXTERIOR
EXT EXTERIOR
FDN FOUNDATION
FES FLARED END SECTION
FTE FLAT FLOOR ELEVATION
FG FRESH GRADE
FND FOUND
FSB FIELD STONE BOUND
FT FOOT LINEAR MEASURE
GAL GALLON
GPM GALLONS PER MINUTE
HDP HIGH DENSITY POLYETHYLENE PIPE
HPT HIGH POINT
HT HEIGHT
I. PIN IRON PIN
I. PIPE IRON PIPE
ID INSIDE DIAMETER
INV INVERT ELEVATION
LP LOW POINT
MAX MAXIMUM
MIN MINIMUM
MUTCD MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES

OC OUTSIDE DIAMETER
OSHA OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PSI POUNDS PER SQUARE INCH
RCP ROUND CONCRETE PIPE
R&S ROUND & STOCKPILE ITEM
SD STONE BOUND
SEMI SEMI MANHOLE
SPH SPHERICAL
SSIB STANDARD SPECIFICATIONS OF HIGHWAYS & BRIDGES, THE COMMONWEALTH OF MASSACHUSETTS DEPARTMENT OF PUBLIC WORKS
STV SLOPED GRANITE CURB

TEB TEMPORARY BENCH MARK
TC CURB ELEVATION
TEH TELEPHONE MANHOLE
TOC TOP OF CONCRETE FOUNDATION ELEVATION
TOP TOP OF RAMP ELEVATION
UP UP
VCTS VERTICAL GRANITE CURB TRANSITION SEGMENT

MATERIAL DEFINITIONS (CONT.)
STRUCTURAL FILL STRUCTURAL FILL IS FIL, OR REPLACEMENT SOIL MATERIALS LOCATED BELOW AND ADJACENT TO ALL STRUCTURAL FOOTINGS, SLABS AND BUILDINGS, (AS DEFINED BY THE MASSACHUSETTS BUILDING CODE) EXTENDING OUT TEN FEET (10'-0") FROM THE EXTERIOR LIMITS OF SUCH STRUCTURES.

STRUCTURAL FILL SHALL MEET THE FOLLOWING REQUIREMENTS - IN THE ORDER OF PRIORITY:

1. A SITE SPECIFIC GEOTECHNICAL REPORT, SPECIFICATION OR REQUIREMENT PREPARED BY A MASSACHUSETTS REGISTERED PROFESSIONAL ENGINEER.

2. A STRUCTURAL ENGINEERS REPORT, SPECIFICATIONS OR REQUIREMENTS.

3. AN ARCHITECT'S REPORT, SPECIFICATION OR REQUIREMENTS.

4. CRUSHED STONE BEING 3/4" TO 1 1/2" DIAMETER, MEETING SSIB M2.0.1.0.

NOTE: ALL SUPPLEMENTAL DATA SUBMITTED IN CONJUNCTION WITH THIS PROJECT AS REQUIRED BY THE TOWN OF LITTLETON REGULATIONS IS HEREBY INCORPORATED AS PART OF THE PLAN SET. THIS PLAN, ITS SUPPORTING DOCUMENTATION AND FORM-WORK ARE SUBMITTED PURSUANT TO THE PROVISIONS OF THE TOWN OF LITTLETON'S SUBDIVISION REGULATIONS AND MASSACHUSETTS GENERAL LAW, CHAPTER 41 AND PURPOSEFULLY OBTAINS THE PROTECTIONS PROVIDED THEREIN.

GENERAL REVISION NOTE:

PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION.

LEGEND


EXISTING INDEX CONTOUR
PROPOSED INTERMEDIATE CONTOUR

SPOT GRADE SPOT GRADE
STONE WALL STONE WALL
EDGE OF WOODS EDGE OF WOODS
100' YEAR FLOOD LINE 100' YEAR FLOOD LINE

EDGE OF WETLAND EDGE OF WETLAND
25' BUFFER 25' BUFFER
50' BUFFER 50' BUFFER
75' BUFFER 75' BUFFER
100' BUFFER 100' BUFFER

NETLAND NETLAND
NETLAND FLS' NETLAND FLS'
RIVERFRONT RIVERFRONT
100' RIVER BUFFER 100' RIVER BUFFER
200' RIVER BUFFER 200' RIVER BUFFER

STATION BARRIER STATION BARRIER
BUILDING SETBACK LINE BUILDING SETBACK LINE



GREAT ROAD (ROUTE 2A \$ 119)
VF
A. LESSA
VF
ALLEN, JR.
J. ALLEN
12 FT. EAD-4
PENNSYLVANIA
MAN
SIGN SIDE

MANNION PLACE

HOWARD E. ALLEN
PATRICIA J. ALLEN

DIANNE M. LESSA
N/F

PLAN BOOK 776 PLAN 23

ELAINE M. & JOHN LINDGREN
TRUSTEES OF LINDGREN
GREAT ROAD REALTY TRUST
BK. 45,713 PG. 243

TIMOTHY M. & HEIDI J.
WILEY

PLAN BOOK 776 PLAN 23

GREAT ROAD (ROUTE 2A & 119)

Proposed Sign:
12' H. x 10' W.
SLEEVE AND GATE
10' DCL
PROPOSED SIGN
21' S.7' EACH SIDE

Proposed Sign:
12' H. x 10' W.
SLEEVE AND GATE
10' DCL
PROPOSED SIGN
21' S.7' EACH SIDE

DIANNE M. LESSA
NF

HOWARD E. ALLEN, JR.
PATRICIA J. ALLEN
NF

ELAINE M. & JOHN LINDGREN
TRUSTEES OF LINDGREN
GREAT ROAD REALTY TRUST
BK. 45,713 PG. 243

TIMOTHY M. & HEIDI J. WILEY
NF

JEFFREY A. & LANETTE M. SUNDQUIST BK.
33,463 PG. 586

PAUL J. & CYNTHIA M. AVELLA
BK. 42,576 PG. 535

JOHN P. & BERG BK. 45,81
NF

MANNION PLACE

MINUTEMAN UTILITY LANTERN, TYP FOR 4

BUILDING 1
48 Units
FF Elev=238±
7 BAY GARAGE

GENERAL REVISION NOTE:
PREVIOUS PLAN DATED:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERSEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION.

**PERMIT SET
NOT FOR CONSTRUCTION
VILLAGE GREEN
LAYOUT & UTILITIES
PLAN 1 OF 2**

**LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:**

FIFTEEN GREAT ROAD II LLC

SCALE: 1"=40' DATE: FEB 4, 2014

Places Associates, Inc.
Planning, Landscape Architecture,
Civil Engineering, Surveying
256 GREAT ROAD, SUITE 4
LITTLETON, MA 01460
978.486.0334 Ph.
978.486.0447 Fax
places@placesassociates.com

John Carter

PROJECT No.: 11-6303A PLAN No. 6303A CP-4

GENERAL REVISION NOTE:
PREVIOUS PLAN DATE:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE
ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO
AVOID CONFUSION.

PERMIT SET
NOT FOR CONSTRUCTION
VILLAGE GREEN
LAYOUT & UTILITIES
PLAN 1 OF 2

LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:


FIFTEEN GREAT
ROAD II LLC

SCALE: 1"=40' DATE: FEB 4, 2014


Places Associates Inc.


Planning, Landscape Architecture,

PROJECT No.: 11-6303A PLAN No. 6303A CP-4









GENERAL NOTES:

- ROADWAY - WEARING COURSE: 1 1/2"
- BINDER COURSE: 1 1/2"
- SIDEWALK - WEARING COURSE: 1"
- BINDER COURSE: 1"
- ALL PAVEMENT SHALL BE CLASS I TYPE I BITUMINOUS CONCRETE

4" LOAM & SEED ALL DISTURBED SURFACES

20' PAVEMENT (24' BOXWOOD DRIVE)

SHOULDER 4' (12' BOXWOOD DRIVE)

10' (12' BOXWOOD DRIVE)

8" 5' SIDEWALK

MAXIMUM IN CUT 2'

MAXIMUM IN FILL 3'

3/8" FT. PITCH

10°

CAPE COD BERM ON BASE COURSE-SEE DETAIL

VERTICAL BIT. CONC. BERM SET ON BASE COURSE-SEE DETAIL

MAXIMUM 2% PITCH

6" MIN. PROCESSED COMPACTED GRAVEL BASE

8" GRavel BORROW SUBBASE-SSHB M:03.0 TYPE B

4" DENSE GRADED CRUSHED STONE SSSH M:01.7

3' ETC

AS REQUIRED

EXISTING PAVEMENT

WEARING COURSE

BINDER COURSE

2' MIN.

1' MIN. DEPTH

KEYHOLE

SEE ABOVE

EXISTING SUBGRADE - LEVEL & COMPACT IF DISTURBED REMOVE ANY ORGANIC MATERIAL

4" DENSE GRADED CRUSHED STONE SSSH M:01.7

8" GRavel BORROW SUBBASE-SSHB M:03.0 TYPE B

12"

EXISTING SUBGRADE OR COMPACTED SUPPLEMENTAL FILL

6" MIN. PROCESSED COMPACTED GRAVEL BASE

TRANSITION TO EXISTING PAVEMENT

NOT TO SCALE

TYPICAL ROAD CROSS SECTION

NOT TO SCALE

SURFACE TREATMENT (AS REQUIRED)

WEARING COURSE

BINDER COURSE

ROAD

12"

8"

BITUMINOUS CONCRETE CURB MASS. D.P.W. TYPE-3

PLANTING

WEARING COURSE BINDER COURSE

NOTE: TO BE USED WHERE SIDEWALK IS DIRECTLY ADJACENT TO ROADWAY AS NOTED ON PLANS

BITUMINOUS CONCRETE CURB MASS. D.P.W. TYPE-3

THOROUGHLY COMPACTED GRAVEL

WEARING COURSE BINDER COURSE

NOTE: TO BE USED WHERE SIDEWALK IS DIRECTLY ADJACENT TO ROADWAY AS NOTED ON PLANS

5" CONC. PAD W/ 8"X8" BOXWOOD W.M. 2" CLEAR ALL SIDES CONC. TO BE AIR ENTRAINED & 4,000 PSI @ 28 DAYS

8" GRavel BORROW, COMPACTED TO 95% MODIFIED PROCTOR

POLYURETHANE SEALANT COLOR TO MATCH CONCRETE

1/4" SMOOTH STAINLESS STEEL ROD, COAT ONE END WITH GREASE & WRAP IN FABRIC, EMBEL BOTH SIDES 8" MIN.

2" TROWELLED EDGE BROOM FINISH

1/2" EXPANSION JOINT FILLER

NOTES:

1. EXPANSION JOINTS REQUIRED AS SHOWN OR EVERY 36'-0" FEET OF PAD O.C.
2. 10" CONCRETE DEPTH FOR ALL PADS FOR GENERATORS OR HEAVY LOAD USES (DUMPSTERS/COMPACTORS).
3. NO ASPHALT IMPREGNATED FELT ALLOWED FOR EXPANSION JOINTS.

CAPE COD BERM

NOT TO SCALE

CONTINUOUS 5/8" EXPANSION JOINT REQUIRED AT INTERFACE BETWEEN CURBING AND WALKS, STRUCTURES OR PERMANENT OBJECTS.

VERTICAL GRANITE CURB UNIT

VERT. GRANITE CURB TO BE USED IN LOCATIONS AS SHOWN ON PLAN.

SAWN TOP-SPLIT FACE

6" REVEAL

BIT. CONC. PAVEMENT DEPTH PER PLAN

4" DENSE GRADED CRUSHED STONE

8"

GRANULE BORROW SUBBASE

THOROUGHLY COMPACTED GRAVEL

6"X6" CONTINUOUS BACKER BEAM OF 4,000 PSI OF UNFORMED CONCRETE

UNDISTURBED EARTH

NOTE: MAXIMUM VERTICAL EDGE HEIGHT BETWEEN SURFACES IS 1/4" IN ALL DIRECTIONS.

FLUSH WALK/PAVEMENT INTERFACE

NOT TO SCALE

1" ± 8"

6" PER CONSTRUCTION SPECS.

SET JOINT PER SLOPED GRANITE CONSTRUCTION SPECS.

SLOPED CURBING

FINISH GRADE

VERTICAL GRANITE CURB

NOT TO SCALE

DESIGN DATA & GENERAL NOTES

1. CONCRETE STRENGTH f'c 5,000 PSI @ 28 DAYS, DENSITY 150 PCF.
2. CEMENT, PORTLAND TYPE I OR II PER ASTM C109-81.
3. ADMIXTURES, AIR & PLASTICIZERS PER ASTM C233-82.
4. AIR ENTRAINMENT 5% - 7%
5. APPROX. WEIGHT: 360LBS.

PARKING WHEEL STOP

NOT TO SCALE

10"

2-1/2"

6"

3"

1' - 6"

10"

3"

1' - 6"

3-ND. 3 REBARS

REBAR ANCHORS, 2 PER CURB STOP EMBED IN BITUMINOUS CONCRETE 10" MIN.

PLAN VIEW

COLD ROLLED 7/8"

STEEL POST, 10' MIN. HT.

SIGN TYPE AS REQUIRED UNIVERSAL SYMBOLS REQUIRED WITH TEXT 0.10 GAGE ALUMINUM SIGN MEETING MHD SSSH CRITERIA.

HEIGHT AS REQUIRED 7'-0" MIN.

BREAK-AWAY BASE TOP 6" ABOVE FIN. GRADE SURFACE TREATMENT AS REQUIRED

6" # 3,000 PSI CONC. EARTHFORMED FOUNDATION SET ON UNDISTURBED SUBGRADE ATTACH (2) 13/16"X4" BOLTS FOR ANCHORS, CAST-IN.

ELEVATION

TYPICAL SITE SIGN

NOT TO SCALE

24" WIDE DETECTABLE SURFACE TILES (TYP. SEE FLUSH WALK/PAVEMENT INTERFACE SET AL)

WALK

HAMP

6'-0"

AS RECD. 5'-0" MIN.

RAMP

12'-1" MAX. (HORZ/VERT)

WOTH AS RECD. 4'-0" MIN.

PLAN VIEW

FINISH GRADE

CURBING (AS RECD)

LANDING

8" MAX

TRANSITION CURB

TYPE 2 ACCESSIBLE RAMP

NOT TO SCALE

ALL STALLS TO BE PAINTED WITH THE INTERNATIONAL SYMBOL OF ACCESSIBILITY, BLUE ON AROUND, WHITE SYMBOL, WHITE BORDER.

TYPE 2 ACCESSIBLE RAMP

SIGN (TYP. FOR EACH SPACE, SEE NOTE 5)

6" WIDE CONTRAST PAINTED LINES WITH 6" DEEP, 1/2" WIDE, 1/2" CENTER LINES, OTHER ASPIRED HIGH CONTRAST DELINEATION

CURB OR BERM AS DEPICTED (SEE PLAN)

NOTES:

- 1) PARKING SPACES SHALL MEET THE REQUIREMENTS OF THE CODE OF MASSACHUSETTS ARCHITECTURAL ACCESS BOARD - 521CM.
- 2) PARKING SPACES AND ACCESS ISLES SHALL BE LEVEL WITH SURFACE SLOPES NOT EXCEEDING 1:10 (2%) IN ALL DIRECTIONS AS MEASURED USING A TWO-FOOT LONG "SMART LEVEL". NO ALLOWANCES CAN BE MADE FOR ANY SURFACE IN ANY DIRECTION - GREATER THAN 2%.
- 3) VAN ACCESSIBLE SPACES ANDISLES SHALL BE A MINIMUM 8'-0" WIDE, A MINIMUM OF ONE VAN SHALL BE PROVIDED PER SITE.
- 4) TWO ACCESSIBLE SPACES MAY SHARE A COMMON ACCESS ISLE.
- 5) A SIGN IDENTIFYING ACCESSIBLE PARKING SPACES AS RESERVED SHALL BE LOCATED AT THE HEAD OF EACH SPACE AND NO MORE THAN 10' FROM THE HEAD OF THE VAN ACCESSIBLE SPACE. THE SIGN SHALL BE AS DESCRIBED BY THE CODE OF MASSACHUSETTS TRAFFIC CONTROL DEVICES (MUTCD), R7-8 OR APPROVED EQUAL.
- 6) SIGNS AT THE HEAD OF VAN ACCESSIBLE SPACES SHALL INCLUDE THE WORDS "VAN ACCESSIBLE", R7-8A

ACCESSIBLE PARKING SPACES

NOT TO SCALE

PERMIT SET

NOT FOR CONSTRUCTION

GENERAL REVISION NOTE:

PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION

VILLAGE GREEN SITE DETAILS


LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR: FIFTEEN GREAT ROAD II LLC


SCALE: AS SHOWN DATE: FEB 4, 2014


Places Associates, Inc.

Planning, Landscape Architecture, Civil Engineering, Surveying

256 GREAT ROAD, SUITE 4
LITTLETON, MA 01480
978.486.0334 Ph.
978.486.0447 Fax
places@placesassociates.com







SECTION A-A'

STORMWATER TREATMENT UNIT

NOT TO SCALE

SCHEDULE OF DRAINAGE STRUCTURES

STRUCTURE	RIM ELEV.	INVERT IN	DIA. (IN.)	INVERT OUT	OUTLET PIPE
DMH A	235.00	TRENCH DRAIN	12"	228.80	70' 12" HDPE S=0.005 FT/FT (RECHARGE)
DCTB B	235.50		12"	232.50	116' 12" HDPE S=0.005 FT/FT (FES**)
LCTB C	238.80		12"	235.07	45' 12" RCP S=0.01 FT/FT (DMH F)
CTB D	239.20		12"	235.70	13' 12" RCP S=0.014 FT/FT (DMH F)
CTB E	239.20		12"	235.70	18' 12" RCP S=0.01 FT/FT (DMH F)
DMH F	239.66	235.52 (CTB D&E) 234.62 (LCTB C)	12"	234.62	75' 12" RCP S=0.015 FT/FT (DMH G)
DMH G	240.36	233.50 (DMH F) 233.06 (DMH K)	12"	232.56	80' 18" RCP S=0.005 FT/FT (DMH H)
DMH H	240.20	232.16 (DMH G)	18"	232.16	95' 18" RCP S=0.005 FT/FT (STORM UNIT*)
STORM UNIT*	237.80	231.69 (DMH H)	18"	231.69	36' 18" RCP S=0.005 FT/FT (FES**)
CTB M	237.50		8"	235.30	18' 8" RCP S=0.01 FT/FT (DMH O)
CTB N	237.50		8"	235.30	13' 8" RCP S=0.014 FT/FT (DMH O)
DMH O	237.60	235.12 (CTB M&N)	8"	235.12	115' 8" RCP S=0.005 FT/FT (DMH L)
DMH L	239.50	234.54 (DMH O)	8"	234.54	87' 8" RCP S=0.005 FT/FT (DMH K)
CTB I	238.30		12"	235.30	12' 12" RCP S=0.01 FT/FT (DMH K)
CTB J	238.30		12"	235.30	19' 12" RCP S=0.008 FT/FT (DMH K)
DMH K	238.35	235.18 (CTB I&J) 233.76 (DMH O)	12"	233.76	140' 12" RCP S=0.005 FT/FT (DMH G)
CTB P	237.50		12"	235.00	11' 12" RCP S=0.01 FT/FT (DMH R)
CTB Q	237.50		12"	235.00	19' 12" RCP S=0.006 FT/FT (DMH R)
DMH R	237.85	235.18 (CTB P&Q)	12"	234.89	111' 12" RCP S=0.005 FT/FT (FES**)

* STORM UNIT = TREATMENT UNIT, SEE STORMWATER TREATMENT UNIT DETAIL


** FES = FLARED END SECTION, SEE DETAILS AND PLANS FOR LOCATION AND INVERT

STORMWATER TREATMENT UNITS:

DMH R - CDS 2015-4
DMH H - CDS 2015-4
DMH 4-65 (BOXWOOD) - CDS 2015-4
DMH 8-85 (BOXWOOD) - CDS 2015-4
DMH 14-50 (BOXWOOD) - CDS 2015-4
TRENCH DRAIN - CDS 2015-4


BASIN NO.	TOP BERM	OUTLET STRUCTURE			OVERFLOW WEIR				
		ORIFICE SIZE	ELEV.	HORIZ. VERT.	INVERT SIZE	INLET	OUTLET ELEV.		
A	237.0	4"	233.00	V	12"	232.50	232.30	234.50	8'
B	237.5	4"	235.00	V	12"	235.00	234.67	236.50	10'
C	234.90	4"	233.00	V	8"	233.00	232.80	233.80	15'
D	233.3	8"	229.50	V	24"	228.40	228.00	231.80	10'

* V-NOTCH WEIR, SEE OUTLET STRUCTURE DETAIL




BASIN "D" OUTLET STRUCTURE

NOT TO SCALE




ROUND OUTLET CONTROL STRUCTURE

NOT TO SCALE



BASIN BERM CROSS SECTION

NOT TO SCALE



LEVEL SPREADER/BASIN OVERFLOW

NOT TO SCALE

200LB. RIP-RAP SPECIFICATIONS:


1. ALL STONE SHALL BE CLEAN DURABLE ANGULAR STONE MEETING THE FOLLOWING SPECIFICATIONS:

STONE SIZE	% OF WEIGHT SMALLER THAN GIVEN SIZE
200 LB.	100%
100 LB.	75%
75 LB.	50%
50 LB.	25%
10 LB.	10%

2. THE RIP-RAP SHALL BE UNLAYED WITH A FILTER BLANKET CONSISTING OF CLEAN, COARSE GRAVEL AND NO STONES OVER 4" IN LONGEST DIMENSION AND NO FEMER THAN 10% OF TOTAL VOLUME PASSING A 200F SIEVE.


3. THE FILTER BLANKET NEED NOT BE COMPAKTED, BUT SHALL BE GRADED TO A UNIFORM THICKNESS OF 12".

4. THE FILTER BLANKET SHALL BE OVERLAYER WITH A STRUCTURAL/EROSION CONTROL FABRIC OF THE TYPE SPECIFIED. SUCH FABRIC SHALL BE CONTINUOUS IN LENGTH, EITHER PARALLEL OR PERPENDICULAR TO THE SLOPE AND MUST BE UNDER ALL RIP-RAPPED SURFACES.




REINFORCED OVERFLOW BROAD-CRESTED WEIR

NOT TO SCALE



FLARED END SECTION/HDPE PIPE CONNECTION

NOT TO SCALE



FLARED END RIP-RAP INLET/OUTLET

NOT TO SCALE

GENERAL REVISION NOTE:

PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION

VILLAGE GREEN DRAINAGE DETAILS



LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:

FIFTEEN GREAT ROAD II LLC

SCALE: AS SHOWN DATE: FEB 4, 2014




Places Associates, Inc.

Planning, Landscape Architecture, Civil Engineering, Surveying
256 GREAT ROAD, SUITE 4
LITTLETON, MA 01460
978.486.0334 Ph.
978.486.0447 Fax
places@placesassociates.com


PROJECT No. 11-6303A PLAN No. 6303A CP-12

NOTES



- ROADWAY PATCH AND BASE/SUB-BASE SHALL BE INSTALLED AS DIRECTED BY THE HIGHWAY SUPERINTENDENT.
- BEDDING, BLANKET, & BACKFILL MATERIALS SHALL BE COMPAKTED TO 90% MAXIMUM DENSITY (MODIFIED PROCTOR) AT OPTIMUM MOISTURE CONTENT FOR BOTH CROSS COUNTRY AND ROADWAY INSTALLATION.
- ALL MATERIALS, INSTALLATION TECHNIQUES, PROCEDURES, INSPECTIONS, AND TESTING SHALL BE IN COMPLIANCE WITH THE REQUIREMENTS OF THE SEWER RULES AND REGULATIONS UNLESS OTHERWISE APPROVED BY THE SEWER SUPERINTENDENT IN WRITING.



FORCEMAIN DISCHARGE
NOT TO SCALE



DROP SEWER MANHOLE DETAIL
NOT TO SCALE



NOTES:
THE SEPARATION OF WATER MAINS AND SEWERS SHALL COMPLY WITH THE FOLLOWING GENERAL REQUIREMENTS.

A. PARALLEL INSTALLATION:

- NORMAL CONDITIONS: THE INSIDE EDGE OF A WATER MAIN SHALL BE LAID AT LEAST 10 FEET HORIZONTALLY FROM THE INSIDE EDGE OF ANY SANITARY SEWER, STORM SEWER OR SEWER MANHOLE.
- WHEN LOCAL CONDITIONS PREVENT A HORIZONTAL SEPARATION OF 10 FEET, ONE OF TWO METHODS MAY BE EMPLOYED, IN BOTH CASES THE INVERT OF THE WATER LINE MUST BE AT LEAST 18" ABOVE THE CROWN OF THE SEWER LINE.


(a) LAY WATER AND SEWER IN SEPARATE TRENCHES

- LAY THE WATER AND SEWER IN THE SAME TRENCH WITH THE WATER MAIN AT ONE SIDE ON A BENCH OF UNDISTURBED EARTH WITH A MINIMUM HORIZONTAL SEPARATION FROM INSIDE PIPE TO INSIDE PIPE OF 30"


B. CROSSINGS:

- WHEN SEWERS MUST CROSS UNDER WATER MAINS, THE SEWER LAID SUCH THAT THE INVERT OF THE WATER LINE IS AT LEAST 18 INCHES ABOVE THE CROWN OF THE SEWER LINE.
- WHEN THE SEWER ELEVATION CANNOT BE VARIED TO MEET THE REQUIREMENT, THE WATER LINE MUST BE RELOCATED OR RECONSTRUCTED WITH MECHANICAL JOINT CEMENT LINED DUCTILE IRON PIPE FOR A DISTANCE OF 10 FT ON EACH SIDE OF THE SEWER.
- WHEN IT IS IMPOSSIBLE TO OBTAIN EITHER OR BOTH OF THE ABOVE REQUIREMENTS, BOTH THE WATER AND SEWER LINES SHALL BE CONSTRUCTED OF MECHANICAL JOINT CEMENT LINED DUCTILE IRON OR OTHER EQUIVALENT MATERIAL, BOTH PIPES SHALL BE PRESSURE TESTED BY AN APPROVED METHOD TO ASSURE WATER TIGHTNESS OR BOTH PIPES SHALL BE ENCASED IN CONCRETE.

SEWER LINE CROSSING-WATER LINE
NOT TO SCALE



PLAN



PRESSURE RELEASE VALVE MANHOLE
NOT TO SCALE

PERMIT SET
NOT FOR CONSTRUCTION

GENERAL REVISION NOTE:
PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DOUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION

VILLAGE GREEN
SEWER DETAILS

LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:

FIFTEEN GREAT
ROAD II LLC

SCALE: AS SHOWN DATE: FEB 4, 2014

Places Associates, Inc.

Planning, Landscape Architecture,
Civil Engineering, Surveying

256 GREAT ROAD, SUITE 4
LITTLETON, MA 01460
978.486.0334 Ph.
978.486.0447 Fax

places@placesassociates.com

PROJECT No. 11-8303A PLAN No. 8303A CP-13

MATERIALS
1 - DESCRIPTION
 1.1 The scope of the specifications shall govern for all materials used in the construction of water distribution facilities under the jurisdiction of the Littleton Water Department. Projects that would necessarily involve materials other than those indicated in this specification shall be subject to the approval of the Water Department Superintendent. Contracts involving materials not covered in this section shall be submitted for approval. Any material used other than materials specified in these specifications shall be submitted for approval and shall be subject to the requirements of this section.

1.1.1 All products included in this section - shall conform to the requirements of the standard specifications referenced herein.

1.1.2 Materials Standard:

A. 100% Portland Cement Mortar Liner For Ductile Iron Pipe and Gray Iron Pipe and Fittings For Water.

B. ANSI A21.10C - 1/2" - 11" Gray Iron and Ductile Iron Fittings, 3" through 48", for Water and Other Liquids.

C. AHSI A21.10C - 1/2" - 11" Rubber Gasket Joints for Ductile Iron and Gray Iron Pressure Pipe, and Fittings.

D. ANSI A21.10C - 1/2" - 11" Ductile Iron Pipe.

E. AHSI A21.10C - 1/2" - 11" Ductile Iron Fittings and Pipe, Class 25, 250, and 800.

F. ASTM A136 - Gray Iron Castings w/ Wheel, Flanges, and Pipe Fittings.

G. ASTM B92 - Composition Spheres w/ Cancer Metal Castings.

H. AHSI A21.10C - 1/2" - 11" Ductile Iron Pipe.

I. AHSI A21.10C - 1/2" - 11" Ductile Iron Pipe Fittings.

J. AHSI A21.10C - 1/2" - 11" Ductile Iron Pipe.

K. AHSI A21.10C - 1/2" - 11" Ductile Iron Pipe Valves.

L. AHSI A21.10C - 1/2" - 11" Ductile Iron Pipe Fittings for Water and Hydrants.

2 - DUCTILE IRON WATERMAINS

2.1 General - Only pipe material listed in this section shall be used for main extensions unless specifically authorized in writing by the Superintendent.

2.2 Ductile Iron Pressure Pipes:

2.2.1 Ductile Iron Pressure Pipes shall be designed in accordance with AHSI A21.10C and ANSI/AHSI A21.10C-11, Class 25 and shall have push-on joints where specified. Pipe shall be double cemented with seal coat inside and out conforming to AHSI A21.10C-11, Class 25.

2.2.2 Pipe shall be designed to withstand a minimum pressure of 250 psi at the point of application.

2.2.3 The pipe manufacturer shall supply with these specifications and certification that each piece of ductile iron pipe has been tested at the factory with full impression test, Ring Sealing or other approved test to fully verify the test.

2.2.4 Pipe shall not be required to fail to meet any of the requirements of this specification.

3 - SERVICE LINES (See Attachment A)

3.1 Description:

The service line is the line from the water main to the customer's property. It shall consist of the corporation pipe at the main, the baring or pipe, the customer's pipe, and the pipe from the customer's pipe to the fixture. LWD also requires a Pressure Reducer be installed past the meter, as well as for all 1/2" Cycles in the service line with a Flow Test Valve in Breaker located in Water Main.

3.1.1 Plastic/Polybutene Service Pipe - Tubing for services shall be polybutene designed for 200 psi service. Pipe shall be in accordance with AHSI A21.10C standard for Polybutene Pressure Pipe, tubing and fittings.

3.1.2 Copper Service Pipe - Copper pipe shall be type approved in section 2 or water main shall be used.

3.2 Requirements: PIP tubing may be required to meet any of the requirements of this specification.

4 - FITTINGS

4.1 Description:

All fittings used in the construction of water lines shall be "Lindstrand Lumber" (LL) as approved.

All materials listed in this section shall be manufactured in the U.S.A., unless specifically authorized in writing by the Superintendent.

4.2 Fittings for Ductile Iron Pipe:

4.2.1 Ductile Iron Pipe fittings conforming to AHSI A21.10C-11, Class 25 or equivalent. Joints shall be furnished with ductile iron sealing glands. Retaining glands shall be ROMAC INDUSTRIES INC. GRIP RING - PIPE RETAINING RINGS, or an approved equivalent. Glands used, gasket used, and pipe shall be as required by the Superintendent.

4.2.2 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.3 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.4 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.5 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.6 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.7 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.8 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.9 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.10 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.11 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.12 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.13 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.14 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.15 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.16 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.17 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.18 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.19 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.20 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.21 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.22 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.23 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.24 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.25 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.26 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.27 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.28 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.29 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.30 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.31 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.32 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.33 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.34 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.35 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.36 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.37 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.38 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.39 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.40 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.41 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.42 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.43 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.44 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.45 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.46 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.47 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.48 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.49 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.50 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.51 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.52 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.53 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.54 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.55 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.56 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.57 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.58 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.59 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.60 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.61 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.62 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.63 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.64 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.65 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.66 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.67 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.68 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.69 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.70 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.71 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.72 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.73 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.74 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.75 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.76 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.77 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.78 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.79 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.80 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.81 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.82 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.83 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.84 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.85 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.86 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the point of application.

4.2.87 Ductile Iron Pipe fittings shall be designed to withstand a minimum pressure of 250 psi at the

DRAINAGE SYSTEM OPERATIONS & MAINTENANCE PLAN

STORM WATER COLLECTION SYSTEM:

THE STORMWATER COLLECTION SYSTEM SERVING THIS SITE IS INTENDED TO BOTH COLLECT STORMWATER RUNOFF AND TO PROVIDE TREATMENT OF THE STORMWATER PRIOR TO IT ENTERING THE DRAINAGE BASINS. THE SYSTEM IS DESIGNED TO PREVENT SPILLS FROM ENTERING THE SITE THROUGH THE USE OF CATCHBASINS. EACH CATCHBASIN IS EQUIPPED WITH A FOUR (4") FOOT DEEP SUMP (WHICH COLLECTS SEDIMENTS AND DEBRIS) AND A OIL/GAS TRAP (WHICH PREVENTS THE INTRUSION OF HYDROCARBONS AND OTHER FLOATING MATERIALS FROM ENTERING THE DRAINAGE SYSTEM). WHEN THESE TWO BASIC CONTROL MECHANISMS ARE FUNCTIONING PROPERLY THEY PROVIDE FOR A REDUCTION OF CONTAMINANTS AND DEBRIS ENTERING THE STORMWATER COLLECTION AND RECHARGE SYSTEMS, AND THEREFORE DOWNSTREAM RECEIVING WATERS/WETLANDS.

THIS SITE IS ALSO SERVED BY INFILTRATION SYSTEMS WHICH COLLECT THE GENERATED RUNOFF AND RECHARGE IT TO THE GROUND, THIS PROVIDING RECHARGE SIMILAR TO THAT OF THE PRE-DEVELOPMENT CONDITION AND FILTERING THE RUNOFF AS IT TRAVELS THROUGH THE EXISTING SOILS TO THE GROUNDWATER TABLE.

BOTH OF THE ABOVE-DESCRIBED SYSTEMS RELY UPON PROPER MONITORING, OPERATIONS AND MAINTENANCE TO FUNCTION AS DESIGNED AND INTENDED. A PROGRAM OF MONITORING, OPERATIONS AND MAINTENANCE MUST BE ONGOING THROUGHOUT THE LIFE AND USE OF THE SITE. THE FOLLOWING ARE THE MAJOR ACTIVITIES, AS DESCRIBED BELOW, ARE TO BE INITIATED AFTER COMPLETION OF THE PROJECT AND ARE NOT RELATED TO THE CONSTRUCTION OF THE SITE, EXCEPT AS SPECIFICALLY PROVIDED. THIS PLAN IS SPECIFICALLY FOR SITE-RELATED ACTIVITIES, NOT ACTIVITIES WHICH ARE INTERIOR TO BUILDINGS, THOUGH THERE ARE NECESSARY IMPLICATIONS AND CORRELATIONS BETWEEN THE TWO.

MONITORING:

THE DRAINAGE SYSTEMS ARE REQUIRED TO BE MONITORED BY THE PROPERTY MANAGER, WHO SHALL DIRECT AN INDIVIDUAL TO ACT AS THE SYSTEM'S MANAGER. THE NAME, ADDRESS AND DAY AND NIGHT (OR EMERGENCY) TELEPHONE NUMBER OF THIS PERSON OR ENTITY SHALL BE PROVIDED TO THE LITTLETON CONSERVATION COMMISSION PRIOR TO THE ISSUANCE OF A CERTIFICATE OF COMPLIANCE FOR THE SITE CONSTRUCTION. THIS INDIVIDUAL SHALL BE RESPONSIBLE FOR A LOT OF THE DRAINAGE SYSTEMS, MAINTENANCE AND MAINTENANCE ACTIVITIES. DRAINAGE SYSTEM COMPONENTS SHALL BE REFERRED TO BY SPECIFIC LOCATION OR THE DESIGN PLAN DESIGNATION, (E.G. CTB # 10) TO AVOID CONFUSION OR MISIDENTIFICATION. THE LOG SHALL BE MADE AVAILABLE TO THE CONSERVATION COMMISSION WITHIN TEN (10) DAYS OF A WRITTEN REQUEST BY THAT AGENCY.

MONITORING FOR THIS SITE SHALL CONSIST OF THE FOLLOWING:

1. ALL CATCHBASINS SHALL BE INSPECTED TO ENSURE THAT THEY ARE WATER-TIGHT (HOLDING WATER HAVE ADEQUATE SUMP CAPACITY, ALL OIL/GAS TRAPS ARE IN-PLACE, ALL CATCHBASIN FRAMES ARE FREE FROM STRUCTURAL DAMAGE, AND ARE DRAINING FREELY. THIS MONITORING SHALL OCCUR AT A MINIMUM OF THREE (3) MONTH INTERVALS (QUARTERLY).

2. ALL DRAINAGE MANHOLES SHALL BE INSPECTED TO ENSURE THAT THEY ARE WATER-TIGHT, ALL LIDS AND FRAMES ARE FREE FROM STRUCTURAL DAMAGE, ARE DRAINING FREELY AND ARE NOT PONDING WATER. THIS MONITORING SHALL OCCUR A MINIMUM OF ONE PER YEAR.

3. OTHER DRAINAGE SYSTEMS SHALL BE INSPECTED TO ENSURE THAT NO EROSION IS OCCURRING AT OUTLETS, ALL OUTLETS ARE FREE-FLOWING AND NO DAMAGE HAS OCCURRED AS PART OF SITE MAINTENANCE OR ACTIVITIES.

OPERATIONS:

1. GOOD HOUSE KEEPING AND MATERIAL MANAGEMENT REDUCE THE RISK OF SPILLS OR OTHER ACCIDENTAL EXPOSURE OF MATERIALS AND SUBSTANCES TO STORMWATER RUNOFF. A POLLUTION PREVENTION PLAN SHALL BE DEVELOPED WHICH SHALL INCLUDE THE FOLLOWING AT A MINIMUM:

A. ALL MATERIALS STORED ON-SITE WILL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR APPROPRIATE CONTAINERS AND, IF POSSIBLE, UNDER A ROOF OR OTHER ENCLOSURE.

B. PRODUCTS SHALL BE KEPT IN THEIR ORIGINAL CONTAINERS WITH THE ORIGINAL MANUFACTURER'S LABEL.

C. SUBSTANCES SHOULD NOT BE MIXED WITH ONE ANOTHER, UNLESS RECOMMENDED BY THE MANUFACTURER.

D. IF POSSIBLE, ALL OF A PRODUCT WILL BE USED UP BEFORE DISPOSING OF A CONTAINER.

E. THE SYSTEM'S MANAGER SHALL INSPECT THE SITE DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS ON SITE, DURING ALL CONSTRUCTION PHASES.

F. ORIGINAL MATERIALS LABELS AND MATERIAL SAFETY DATA SHEETS SHALL BE KEPT; THEY ARE REQUIRED FOR SPILL RESPONSE.

G. PETROLEUM PRODUCTS:

1) ALL ON-SITE VEHICLES AND PARKING AREAS SHALL BE REGULARLY MONITORED FOR LEAKS AND RECEIVE REGULAR PREVENTIVE MAINTENANCE TO PREVENT LEAKAGE.

2) PETROLEUM PRODUCTS SHALL BE STORED UNDER COVER AND SHALL BE IN TIGHT, SEALED CONTAINERS WHICH ARE CLEARLY LABELED.

H. FERTILIZERS:

1) FERTILIZERS SHALL ONLY BE USED IN THE MINIMUM AMOUNTS AS RECOMMENDED BY THE MANUFACTURER.

2) THE CONTENTS OF ANY UNUSED FERTILIZER SHALL BE TRANSFERRED TO A CLEAN, DRY, SEALED PLASTIC BIN TO AVOID SPILLAGE.

I. PAINTS, SOLVENTS:

1) ALL PAINTS AND SOLVENTS SHALL BE STORED IN ORIGINAL MANUFACTURER'S CONTAINERS IN A COVERED LOCATION.

2. SPILL CONTROL PRACTICES:


A. MANUFACTURER RECOMMENDED METHODS SHALL BE CLEARLY POSTED FOR SPILL CLEANUP. ALL PERSONNEL SHALL BE MADE AWARE OF THE PROCEDURES AND THE LOCATIONS OF CLEANUP INFORMATION AND SUPPLIES.

B. MATERIAL AND EQUIPMENT NECESSARY FOR SPILL CLEANUP WILL BE KEPT ON-SITE IN A DESIGNATED MATERIAL STORAGE AREA. EQUIPMENT WILL INCLUDE, BUT NOT BE LIMITED TO: DUMP TRUCKS, PAPER TRUCKS, RAGS, GLOVES, GOGGLES, ABSORBENT MATTER, SAND, SAWDUST, AND PLASTIC & METAL TRASH CONTAINERS SPECIFICALLY KEPT AND LABELED FOR THIS PURPOSE.


C. ALL SPILLS WILL BE CLEANED-UP IMMEDIATELY AFTER DISCOVERY.

D. SPILLS OF TOXIC OR HAZARDOUS MATERIAL OR NATURE WILL BE REPORTED TO THE APPROPRIATE STATE AND LOCAL AGENCIES AND TO THE MANUFACTURER.

E. THE SPILL PREVENTION PLAN WILL INCLUDE PROVISIONS TO ADAPT THE PLAN TO ENSURE THAT SPILLS WILL NOT REOCUR, AND HOW TO CLEANUP THE SPILL IF THERE IS ANOTHER ONE.




NOT TO SCALE




TEMPORARY STOCKPILE


NOT TO SCALE



NOT TO SCALE




NOT TO SCALE




TEMPORARY CONSTRUCTION ENTRANCE

NOT TO SCALE



STRAW WATTERLS


NOT TO SCALE



TEMPORARY DEWATERING AREA

NOT TO SCALE

NOTE: ALL SITE CONSTRUCTION METHODS & MATERIALS SHALL COMPLY TO THE REQUIREMENTS OF THE LITTLETON HIGHWAY DEPARTMENT AND ALL ISSUED ORDERS OF CONDITIONS AND OTHER APPLICABLE FEDERAL, STATE AND LOCAL PERMITS..



NOT TO SCALE

GENERAL REVISION NOTE:
PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION.

VILLAGE GREEN EROSION AND SEDIMENTATION CONTROL PLAN

LOCATION: 15 GREAT ROAD
TOWN: LITTLETON, MASSACHUSETTS
PREPARED FOR:

FIFTEEN GREAT
ROAD II LLC


SCALE: AS NOTED DATE: FEB 4, 2014

Places Associates, Inc.


Planning, Landscape Architecture,
Civil Engineering, Surveying


256 GREAT ROAD, SUITE 4
LITTLETON, MA 01460
978.486.0334 Ph.
978.486.0447 Fax


places@placesassociates.com




PROJECT NO: 11-6303A PLAN NO: B303A CP-15










INDIVIDUAL UNIT LANDSCAPING:

1. TREES: Tree to be planted for typical individual units would include species such as
 - a. Flowering Dogwoods
 - b. Flowering Crab Apples
 - c. Magnolias
 - d. Arborvitae
 - e. Paperbark Maple
 - f. River Birch
 - g. Flowering Cherry
 - h. Flowering Almond
 - i. Flowering Pear
 - j. Similar, low stature, flowering or accent trees.
2. SHRUBS:
 - Evergreen Shrubs:
 - a. Yew
 - b. Blue Rug Juniper
 - c. Upright Juniper
 - d. Arborvitae
 - e. Accent Pines
 - f. Holly
 - g. Cypress
 - h. False Cypress
 - i. Cedar
 - j. Broad-leaved Evergreens (Rhododendrons, Mountain Laurel, Azalea, Luecothoe)
 - Flowering Shrubs:
 - a. Azalea
 - b. Forsythia
 - c. Enkianthus
 - d. Potentilla
 - e. Spiraea
 - f. Lilac (early & late)
 - g. Inkberry
 - h. Winterberry
 - i. Hydrangea
 - j. Viburnums
 - k. Other similar mid to small size flowering shrubs, with design intent of full seasonal color.
4. Accent & Ground cover:
 - a. Decorative Grasses
 - b. Daylilly
 - c. Perennial Plants
 - d. Pachysandra
 - e. Virginia Creeper
 - f. Hosta
 - g. Other accent and groundcover plants to provide surface stabilization, in fill and aesthetics

- STREET/SHADE TREE
- EVERGREEN TREE
- PINE BUFFER TREE
- FLOWERING/ORNAMENTAL TREE
- EVERGREEN SCREEN
- FLOWERING SHRUB
- EVERGREEN SHRUB
- SMALL FLOWERING SHRUB



NOTES:

1. UNLESS OTHERWISE SHOWN, ALL SURFACES WILL BE LOAMED AND SEDED OR BE LANDSCAPED WITH HARD SURFACES (PAVEMENT).
2. IMMEDIATELY ADJACENT TO ALL BUILDINGS WILL BE A MINIMUM OF THREE FOOT WIDE CRUSHED STONE BED.
3. ALL PLANTS SHALL BE GUARANTEED FOR A MINIMUM OF ONE YEAR FROM THE DATE OF INSTALLATION.
4. ALL PLANTS SHALL MEET THE AMERICAN NURSERYMAN'S ASSOCIATION STANDARDS FOR PLANT STANDARDS, QUALITY AND HEALTH.
5. ALL PLANTING BEDS ARE TO RECEIVE A MINIMUM OF 8" DEPTH OF PLANTING LOAM AND A MINIMUM OF 4" OF SHREDDED BARK MULCH OR OTHER SIMILAR MULCHING MATERIAL.

GENERAL REVISION NOTE:

PREVIOUS PLAN DATES:
DEC 4, 2012-MINOR REVISIONS
DEC 17, 2013-GENERAL REVISION

DUE TO EXTENSIVE REVISIONS, THESE PLANS SUPERCEDE ALL PREVIOUS PLANS AND ARE DATED FEB 4, 2014 TO AVOID CONFUSION.

VILLAGE GREEN

LOCATION: 15 GREAT ROAD TOWN: LITTLETON, MASSACHUSETTS PREPARED FOR:	FIFTEEN GREAT ROAD II LLC
SCALE: 1"=60'	DATE: FEB 4, 2014
Places Associates, Inc.	
Planning, Landscape Architecture, Civil Engineering, Surveying	
256 GREAT ROAD, SUITE 4 LITTLETON, MA 01460 978.485.0334 Ph. 978.486.0447 Fax places@placeassociates.com	

Places Associates, Inc.





